






strip⁺tec™ ST

STRIPTEC ST profiles are designed to join adjoining floors of equal or different type and thickness. The rounded shape of this profile covers edge imperfections and allows a slight rotation, compensating for elevation differences of up to 3/16" (5mm). It can also be used as a termination profile, given a floor thickness of up to 3/16" (5mm). Available in two versions: self-adhesive and screw-on.



Installation of self adhesive version:

- 1) Make sure the base is solid, flat, level, clean and dry.
- 2) Cut the profile to the desired length and remove adhesive backing.
- 3) Press uniformly downwards on to the profile to apply. Do not hammer.

Installation of the pre-drilled version:

- 1) Cut the profile to the desired length and mark the position of the pre-drilled holes.
- 2) Fasten with flathead screws.



STRIPTEC ST-OL* Polished Brass

This laminated polished brass profile is resistant to light chemical and mechanical impact and highly resistant to use and wear. The brass version is especially recommended for elegant residential detailing. Available in pre-drilled and adhesive versions.

STRIPTEC ST-IL* Polished Stainless Steel

This stainless steel profile ensures high resistance to use and wear and good resistance to weathering. Available in self-adhesive (OLA), drilled (OLF), and pre-drilled (OLN) versions.

STRIPTEC ST-A* Anodized Aluminum

This anodized aluminum profile is available in three finishes: silver (AS), gold (AO), bronze (AB). Due to the chromatic variations available, it is especially suited for residential use.

STRIPTEC ST 30* Wood Laminate Aluminum

This melamine laminated aluminum profile is available in eight different finishes. The smoothly-embossed melamine is resistant to abrasion, easy to clean and blends easily with existing floors.

	B = in	mm	Art.	Adhesive	Drilled	Not drill.
Material:	11/16	18	ST 18	OLA	-	OLN
Laminated Brass	1-3/16	30	ST 30	OLA	OLF	-
Finish: Polished (OL*)	1-3/8	35	ST 35	OLA	OLF	-
Length: 8'10" (2.70meters)						
35-7/16" / 4' 5"						
(0.90 / 1.35 meters)						
Width: 11/16", 1-3/16", 1-3/8" (18.30.35mm)						

Material:	11/16	18	ST 18	ILA	-	ILN
Stainless Steel	1-3/16	30	ST 30	ILA	ILF	-
Finish: Polished (IL*)	1-3/8	35	ST 35	ILA	ILF	-
Length: 8'10" (2.70meters)						
35-7/16" / 4' 5"						
(0.90 / 1.35 meters)						
Width: 11/16", 1-3/16", 1-3/8" (18.30.35mm)						

Material:	11/16	18	ST 18	A*A	A*F	
Extruded Anodized Aluminum	1-3/16	30	ST 30	A*A	A*F	
Finish*: Silver (AS*), Gold (AO*), Bronze (AB*)	1-3/8	35	ST 35	A*A	A*F	
	1-9/16	40	ST 40	A*A	A*F	
Length: 8'10" (2.70meters)						
35-7/16" / 4' 5"						
(0.90 / 1.35 meters)						
Width: 11/16", 1-3/16", 1-3/8", 1-9/16" (18.30.35.40mm)						

	Finish	Adhesive	Drilled
Material:	Bleached	ST 30	RSA ST 30
Extruded Aluminum Laminate cov.	Maple	ST 30	ACA ST 30
Length: 8'10" (2.70meters)	Beech	ST 30	FAA ST 30
	Oak	ST 30	ROA ST 30
	Cherry	ST 30	CIA ST 30
Width: 1-3/16" (30mm)	Light walnut	ST 30	NCA ST 30
	Dark walnut	ST 30	NSA ST 30
	Wengé	ST 30	WEA ST 30

Pre-cut length available in SELFLINE kit L= 35-7/16" / 4' 5" (0.90/1.35m)




STRIPTEC ST/SB offers a wide selection of transition and threshold strip profiles available in a variety of widths and finishes. Its surface may be smooth or ribbed, curved or flat to fit under doorways. The brass and aluminum models are suitable for high traffic areas.

strip+tec™ ST/STB



STRIPTEC ST 38 A* Anodized Aluminum


Top surface ribbing offers high corrosion resistance and limited resistance to mechanical impact.
Center thickness = 9/64" (3.7mm).
Available in self-adhesive (A*A) and drilled (A*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Anodized Aluminum	1-1/2	38	ST 38	ASA	ASF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)	1-1/2	38	ST 38	AOA	AOF
			ST 38	ABA	ABF
Length: 8'10" (2.70meters)					
35-7/16" / 4' 5" (0.90/1.35meters)					

STRIPTEC STB-OL* Polished Brass


Brass guarantees excellent resistance to mechanical and chemical impact. This profile is ideal for industrial and commercial heavy-traffic areas as well as elegantly-designed residential spaces.
Center thickness = 1/16" (1.5mm).
Available in self-adhesive (O*A) and drilled (O*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Brass	1-3/16	30	STB 30	OLA	OLF
Finish: Polished (OL*)	1-3/8	35	STB 35	OLA	OLF
	1-9/16	40	STB 40	OLA	OLF
Length: 8'10" (2.70meters)					
35-7/16" / 4' 5" (0.90/1.35meters)					

STRIPTEC ST 50 OL* Polished Brass


This heavy, curved brass profile offers excellent resistance to mechanical and chemical impact, making it ideal for industrial and commercial heavy-trafficked areas.
Center thickness = 3/16" (5mm).
Available in self-adhesive (O*A) and drilled (O*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Brass	2	50	ST 50	OLA	OLF
Finish: Polished (OL*)					
Length: 8'10" (2.70meters)					

STRIPTEC STB 25 A* Anodized Aluminum


This flat, grooved profile offers high corrosion resistance and limited resistance to mechanical impact. It is available in three finishes: silver (AS), gold (AO), bronze (AB).
Center thickness = 3/32" (2.2mm).
Available in self-adhesive (A*A) and drilled (A*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Anodized Aluminum	1	25	STB 25	ASA	ASF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)	1	25	STB 25	AOA	AOF
	1	25	STB 25	ABA	ABF
Length: 8'10" (2.70meters)					
35-7/16" / 4' 5" (0.90/1.35meters)					

STRIPTEC STB 35 A* Anodized Aluminum

This flat, heavy-duty profile is available in three finishes: silver (AS), gold (AO), bronze (AB). The drilled version has holes along the center. Lateral holes may be ordered upon request.
Center thickness = 3/32" (2.4mm).
Available in self-adhesive (A*A) and drilled (A*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Anodized Aluminum	1-3/8	35	STB 35	ASA	ASF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)	1-3/8	35	STB 35	AOA	AOF
	1-3/8	35	STB 35	ABA	ABF
Length: 8'10" (2.70meters)					
35-7/16" / 4' 5" (0.90/1.35meters)					

Pre-cut length available in SELFLINE kit L= 35-7/16" / 4' 5" (0.90/1.35m)